

## AMERICANA™ PORCH FLOORING PERFORMANCE COMPARED TO COMMON PORCH FLOORING MATERIALS

	AMERICANA™ HARDWOOD	PRESSURE TREATED SOFTWOODS	COMPOSITES	DOUGLAS FIR
<b>DURABILITY</b>	25+ YEARS CLASS 1	UP-TO 15 YEARS CLASS 2	20 YEARS CLASS 1	10 YEARS CLASS 4
<b>BEAUTY OF NATURAL WOOD</b>	☑	☑	⊗	☑
<b>SUSTAINABLE</b>	☑	☑	⊗	☑
<b>CHEMICAL FREE</b>	☑	⊗	⊗	☑
<b>HARDNESS (JANKA)</b>	1400	690	1120	690
<b>FIRE RATING</b>	B	C / D	A / B	B
<b>WEIGHT</b>	40 LBS/CUBIC FOOT	35 LBS/CUBIC FOOT	60 LBS/CUBIC FOOT	31 LBS/CUBIC FOOT
<b>INSECT RESISTANCE</b>	GOOD	GOOD	GOOD	POOR

# AMERICANA™ PORCH FLOORING PERFORMANCE COMPARED TO COMMON PORCH FLOORING MATERIALS

	AMERICANA™ HARDWOOD	PRESSURE TREATED SOFTWOODS	COMPOSITES	DOUGLAS FIR
<b>ENVIRONMENTAL CREDENTIALS</b>	<ul style="list-style-type: none"> <li>• Sustainable American Hardwoods</li> <li>• FSC Certified Available</li> <li>• NO Chemicals</li> <li>• Negative Carbon Footprint</li> </ul>	<ul style="list-style-type: none"> <li>• Sustainable American Softwoods</li> <li>• Infused with Chemicals to Inhibit Rot &amp; Insects</li> <li>• Disposal Difficult</li> </ul>	<ul style="list-style-type: none"> <li>• Synthetic Oil-Based Product</li> </ul>	<ul style="list-style-type: none"> <li>• Sustainable American Softwoods</li> </ul>
<b>MAINTENANCE</b>	<ul style="list-style-type: none"> <li>• Annual Surface Washing</li> <li>• Stains or Oils Maintain Original Color &amp; Finish</li> <li>• Can Be Left Unfinished (Color Turns Silver)</li> </ul>	<ul style="list-style-type: none"> <li>• Annual Cleaning</li> <li>• Stains or Oils Maintain Original Color &amp; Finish</li> </ul>	<ul style="list-style-type: none"> <li>• Annual Cleaning</li> </ul>	<ul style="list-style-type: none"> <li>• Annual Surface Washing (Color Turns Silver)</li> <li>• Stains or Oils Maintain Original Color &amp; Finish</li> </ul>
<b>FEATURES &amp; INSTALLATION</b>	<ul style="list-style-type: none"> <li>• Symmetrical Joints (Easily Use Both Sides of Boards)</li> <li>• Easy to Lift, Cut, Drill &amp; Install</li> <li>• High Dent &amp; Scratch Resistance</li> <li>• Paintable &amp; Stainable</li> </ul>	<ul style="list-style-type: none"> <li>• Standard Installation Methods</li> <li>• Easy to Dent &amp; Scratch</li> </ul>	<ul style="list-style-type: none"> <li>• Consistent Dimensions</li> <li>• Easy to Cut</li> <li>• Swells &amp; Shrinks Longitudinally</li> <li>• Very Hot In Sunlight</li> </ul>	<ul style="list-style-type: none"> <li>• Standard Installation Methods</li> <li>• Easy to Dent &amp; Scratch</li> </ul>